

**ALBERTA TRANSPORTATION AND  
ECONOMIC CORRIDORS GRMP  
NORTH CENTRAL (ATHABASCA AND FORT  
McMURRAY DISTRICTS)  
INSTRUMENTATION MONITORING- SPRING 2024**



Site Number	Location	Name	Hwy	km
NC110	HWY 754:06 C1 32.94	Wabasca Lake Slip 'n Slide	754:06	Km 32.94
<b>Legal Description:</b> NW-27-80-25 W4		<b>UTM Co-ordinates</b>		
		12U E 321468	N	6207205

<b>Current Monitoring:</b>	13-Jun-2024	<b>Previous Monitoring</b>	01-May-2024
<b>Instruments Read By:</b>	Mr. Niraj Regmi, G.I.T and Mr. Nixson Mationg, of Thurber		

Instruments Read During This Site Visit			
<b>Slope Inclinometers (SIs):</b> SI24-2 and SI24-3	<b>Pneumatic Piezometers (PN):</b> N/A	<b>Vibration Wire Piezometers (VW):</b> VW24-2A, VW24-2B, VW24-3A and VW24-3B	<b>Standpipe Piezometers (SP):</b> SP24-1 and SP24-4
<b>Load Cell (LC):</b> N/A	<b>Strain Gauges:</b> N/A	<b>SAA's:</b> N/A	<b>Others:</b>

Readout Equipment Used			
<b>Slope Inclinometers:</b> RST Digital Inclinator probe with a 2 ft. wheelbase and a RST Pocket PC readout.	<b>Pneumatic Piezometers:</b>	<b>Vibration Wire Piezometers:</b> Geokon GK404 digital readout	<b>Standpipe Piezometers:</b> DGSI dipmeter
<b>Load Cell:</b>	<b>Strain Gauges:</b>	<b>SAA's:</b>	<b>Others:</b>

Notes:
<ul style="list-style-type: none"> <li>- A site plan showing instrument locations is included in Appendix A.</li> <li>- SIs plots with A and B directions are presented in Appendix A and summarized in Table NC110-1, attached. Where movement was recorded, the resultant (plot X) and the rate of movement plot are also included.</li> <li>- Standpipe and vibrating wire piezometer plots are included in Appendix A.</li> <li>- Standpipe Piezometer readings are summarized in Table NC110-2, attached.</li> <li>- Vibrating Wire Piezometer readings are summarized in Table NC110-3, attached.</li> </ul>

Discussion	
<b>Zones of New Movement:</b>	A zone of movement was observed in slope Inclinator SI24-3, over 0.6 to 3.7 m depth.
<b>Interpretation of Monitoring Results:</b>	<p>SI24-2 showed a rate of movement of 56.6 mm/yr over 1.8 m to 3.6 m since the previous readings on May 1, 2024. This corresponds to an increase in rate of movement of 60.6 mm/yr.</p> <p>SI24-3 showed a rate of movement of 16.5 mm/yr over 0.6 m to 3.7 m depth since the last readings on February 20, 2024. This corresponds to an increase in the rate of movement by 10.0 mm/yr. The movement zones in both SIs are within the native high plastic clay below the highway embankment fill.</p> <p>Standpipe piezometer SP24-1 and SP24-4 showed increases in groundwater level of 0.86 m and 0.35 m, respectively compared to the last reading on May 1, 2024. The groundwater level in both instruments is the highest since they were initialized.</p>

	<p>Vibrating wire piezometer VW24-2A was found to be malfunctioning during the spring 2024 readings.</p> <p>Vibrating wire piezometers VW24-2B and VW24-3A showed increases in groundwater level of 0.19 m and 1.60 m, respectively, since they were last read on May 1, 2024. The groundwater level recorded in both instruments is the highest since they were initialized. VW24-2B showed a decrease in groundwater level of 0.06 m since the last reading on May 1, 2024.</p>
<b>Future Work:</b>	The instruments should be read again in the fall of 2024.
<b>Instrumentation Repairs:</b>	Vibrating Wire Piezometer VW24-2A should be read again to confirm if it is still malfunctioning. If it continues to malfunction, it should be removed from future readings.
<b>Additional Comments:</b>	

<b>Attachments:</b>	<ul style="list-style-type: none"><li>• Table NC110-1 Spring 2024 – HWY 754:06 Wabasca Lake Slip 'n Slide, Slope Inclinometer Instrumentation Reading Summary</li><li>• Table NC110-2 Spring 2024 – HWY 754:06 Wabasca Lake Slip 'n Slide, Standpipe Piezometer Instrumentation Reading Summary</li><li>• Table NC110-3 Spring 2024 – HWY 754:06 Wabasca Lake Slip 'n Slide, Vibrating Wire Piezometer Instrumentation Reading Summary</li> <li>• Statement of Limitations and Conditions</li> <li>• APPENDIX A – NC110-1 SPRING 2024<ul style="list-style-type: none"><li>○ Field Inspector's report</li><li>○ Site Plan Showing Approximate Instrument Locations (Drawing No. 32122-NC110)</li><li>○ SI Reading Plots</li><li>○ Figure NC110-1 (Piezometric Depths)</li><li>○ Figure NC110-2 (Piezometric Elevations)</li></ul></li></ul>
---------------------	---

We trust this report meets your requirements at present. If you have any questions, please contact the undersigned at your convenience.

Yours very truly,  
Thurber Engineering Ltd.  
Tarek Abdelaziz, Ph.D., P. Eng.  
Partner | Senior Geotechnical Engineer

Lucas Green, P.Eng.  
Geotechnical Engineer



**Table NC110-1: Spring 2024 – Hwy 754:06 Wabasca Lake Slip n’ Slide Inclinometer Instrumentation Reading Summary**

Date Monitored: June 13, 2024

<b>INSTRUMENT #</b>	<b>DATE INITIALIZED</b>	<b>TOTAL CUMULATIVE RESULTANT MOVEMENT AND DEPTH OF MOVEMENT TO DATE (mm)</b>	<b>MAXIMUM RATE OF MOVEMENT (mm/yr)</b>	<b>CURRENT STATUS OF SI</b>	<b>DATE OF PREVIOUS READING</b>	<b>INCREMENTAL MOVEMENT SINCE PREVIOUS READING (mm)</b>	<b>CURRENT RATE OF MOVEMENT (mm/yr)</b>	<b>CHANGE IN RATE OF MOVEMENT SINCE PREVIOUS READING (mm/yr)</b>
SI24-2	February 1, 2024	8.6 over 1.8 m to 3.6 m depth in 236° direction	56.6 in June 2024	Operational	May 1, 2024	6.7	56.6	60.6
SI24-3	February 1, 2024	5.5 over 0.6 m to 3.7 m depth in 228° direction	16.5 in June 2024	Operational	February 20, 2024	5.1	16.5	10.0

Drawing 32122-NC110 in Appendix A provides a sketch of the approximate location of the monitoring instrumentation for this site.



**Table NC110-2: Spring 2024 – Hwy 754:06 Wabasca Lake Slip n’ Slide Standpipe Piezometer Instrumentation Reading Summary**

Date Monitored: June 13, 2024

<b>INSTRUMENT #</b>	<b>DATE INITIALIZED</b>	<b>TIP DEPTH (m)</b>	<b>GROUND ELEV. (m)</b>	<b>CURRENT STATUS</b>	<b>HIGHEST MEASURED GROUNDWATER LEVEL BGS (m)</b>	<b>CURRENT GROUNDWATER DEPTH BGS (m)</b>	<b>PREVIOUS GROUNDWATER DEPTH BGS (May 1, 2024) (m)</b>	<b>CHANGE IN WATER LEVEL SINCE PREVIOUS READING (m)</b>
SP24-1	Jan. 29, 2024	19.40	-	Operational	1.71 on June 13, 2024	1.71	2.57	0.86
SP24-4	Feb. 1, 2024	17.34	-	Operational	3.61 on June 13, 2024	3.61	3.96	0.35

Drawing 32122-NC110 in Appendix A provides a sketch of the approximate location of the monitoring instrumentation for this site.



**Table NC110-3: Spring 2024 – Hwy 754:06 Wabasca Lake Slip n’ Slide Vibrating Wire Piezometer Instrumentation Reading Summary**

Date Monitored: June 13, 2024

<b>INSTRUMENT #</b>	<b>DATE INITIALIZED</b>	<b>TIP DEPTH (m)</b>	<b>GROUND ELEV. (m)</b>	<b>CURRENT STATUS</b>	<b>HIGHEST MEASURED GROUNDWATER LEVEL BGS (m)</b>	<b>CURRENT GROUNDWATER DEPTH BGS (m)</b>	<b>PREVIOUS GROUNDWATER DEPTH BGS (MAY 1, 2024) (m)</b>	<b>CHANGE IN WATER LEVEL SINCE PREVIOUS READING (m)</b>
VW24-2A (171163)	February 2, 2024	3.6	-	<i>Not Functioning</i>	2.64 on May 1, 2024	N/A	2.64	-
VW24-2B (163823)	February 2, 2024	15.0	-	Operational	8.96 on June 13, 2024	8.96	9.15	0.19
VW24-3A (171177)	February 2, 2024	3.7	-	Operational	1.58 on June 13, 2024	1.58	3.18	1.60
VW24-3B (163840)	February 2, 2024	12.1	-	Operational	3.29 on May 1, 2024	3.35	3.29	-0.06

Drawing 32122-NC110 in Appendix A provides a sketch of the approximate location of the monitoring instrumentation for this site.



## STATEMENT OF LIMITATIONS AND CONDITIONS

### 1. STANDARD OF CARE

This Report has been prepared in accordance with generally accepted engineering or environmental consulting practices in the applicable jurisdiction. No other warranty, expressed or implied, is intended or made.

### 2. COMPLETE REPORT

All documents, records, data and files, whether electronic or otherwise, generated as part of this assignment are a part of the Report, which is of a summary nature and is not intended to stand alone without reference to the instructions given to Thurber by the Client, communications between Thurber and the Client, and any other reports, proposals or documents prepared by Thurber for the Client relative to the specific site described herein, all of which together constitute the Report.

IN ORDER TO PROPERLY UNDERSTAND THE SUGGESTIONS, RECOMMENDATIONS AND OPINIONS EXPRESSED HEREIN, REFERENCE MUST BE MADE TO THE WHOLE OF THE REPORT. THURBER IS NOT RESPONSIBLE FOR USE BY ANY PARTY OF PORTIONS OF THE REPORT WITHOUT REFERENCE TO THE WHOLE REPORT.

### 3. BASIS OF REPORT

The Report has been prepared for the specific site, development, design objectives and purposes that were described to Thurber by the Client. The applicability and reliability of any of the findings, recommendations, suggestions, or opinions expressed in the Report, subject to the limitations provided herein, are only valid to the extent that the Report expressly addresses proposed development, design objectives and purposes, and then only to the extent that there has been no material alteration to or variation from any of the said descriptions provided to Thurber, unless Thurber is specifically requested by the Client to review and revise the Report in light of such alteration or variation.

### 4. USE OF THE REPORT

The information and opinions expressed in the Report, or any document forming part of the Report, are for the sole benefit of the Client. NO OTHER PARTY MAY USE OR RELY UPON THE REPORT OR ANY PORTION THEREOF WITHOUT THURBER'S WRITTEN CONSENT AND SUCH USE SHALL BE ON SUCH TERMS AND CONDITIONS AS THURBER MAY EXPRESSLY APPROVE. Ownership in and copyright for the contents of the Report belong to Thurber. Any use which a third party makes of the Report, is the sole responsibility of such third party. Thurber accepts no responsibility whatsoever for damages suffered by any third party resulting from use of the Report without Thurber's express written permission.

### 5. INTERPRETATION OF THE REPORT

- a) Nature and Exactness of Soil and Contaminant Description: Classification and identification of soils, rocks, geological units, contaminant materials and quantities have been based on investigations performed in accordance with the standards set out in Paragraph 1. Classification and identification of these factors are judgmental in nature. Comprehensive sampling and testing programs implemented with the appropriate equipment by experienced personnel may fail to locate some conditions. All investigations utilizing the standards of Paragraph 1 will involve an inherent risk that some conditions will not be detected and all documents or records summarizing such investigations will be based on assumptions of what exists between the actual points sampled. Actual conditions may vary significantly between the points investigated and the Client and all other persons making use of such documents or records with our express written consent should be aware of this risk and the Report is delivered subject to the express condition that such risk is accepted by the Client and such other persons. Some conditions are subject to change over time and those making use of the Report should be aware of this possibility and understand that the Report only presents the conditions at the sampled points at the time of sampling. If special concerns exist, or the Client has special considerations or requirements, the Client should disclose them so that additional or special investigations may be undertaken which would not otherwise be within the scope of investigations made for the purposes of the Report.
- b) Reliance on Provided Information: The evaluation and conclusions contained in the Report have been prepared on the basis of conditions in evidence at the time of site inspections and on the basis of information provided to Thurber. Thurber has relied in good faith upon representations, information and instructions provided by the Client and others concerning the site. Accordingly, Thurber does not accept responsibility for any deficiency, misstatement or inaccuracy contained in the Report as a result of misstatements, omissions, misrepresentations, or fraudulent acts of the Client or other persons providing information relied on by Thurber. Thurber is entitled to rely on such representations, information and instructions and is not required to carry out investigations to determine the truth or accuracy of such representations, information and instructions.
- c) Design Services: The Report may form part of design and construction documents for information purposes even though it may have been issued prior to final design being completed. Thurber should be retained to review final design, project plans and related documents prior to construction to confirm that they are consistent with the intent of the Report. Any differences that may exist between the Report's recommendations and the final design detailed in the contract documents should be reported to Thurber immediately so that Thurber can address potential conflicts.
- d) Construction Services: During construction Thurber should be retained to provide field reviews. Field reviews consist of performing sufficient and timely observations of encountered conditions in order to confirm and document that the site conditions do not materially differ from those interpreted conditions considered in the preparation of the report. Adequate field reviews are necessary for Thurber to provide letters of assurance, in accordance with the requirements of many regulatory authorities.

### 6. RELEASE OF POLLUTANTS OR HAZARDOUS SUBSTANCES

Geotechnical engineering and environmental consulting projects often have the potential to encounter pollutants or hazardous substances and the potential to cause the escape, release or dispersal of those substances. Thurber shall have no liability to the Client under any circumstances, for the escape, release or dispersal of pollutants or hazardous substances, unless such pollutants or hazardous substances have been specifically and accurately identified to Thurber by the Client prior to the commencement of Thurber's professional services.

### 7. INDEPENDENT JUDGEMENTS OF CLIENT

The information, interpretations and conclusions in the Report are based on Thurber's interpretation of conditions revealed through limited investigation conducted within a defined scope of services. Thurber does not accept responsibility for independent conclusions, interpretations, interpolations and/or decisions of the Client, or others who may come into possession of the Report, or any part thereof, which may be based on information contained in the Report. This restriction of liability includes but is not limited to decisions made to develop, purchase or sell land.



**THURBER** ENGINEERING LTD.

**ALBERTA TRANSPORTATION AND ECONOMIC CORRIDORS GRMP (CON0022163)  
NORTH CENTRAL (ATHABASCA AND FORT McMURRAY DISTRICTS)  
INSTRUMENTATION MONITORING RESULTS**

**SPRING 2024**

**APPENDIX A  
DATA PRESENTATION**

**SITE NC110: HWY 754:06 WABASCA LAKE SLIP N' SLIDE**



ALBERTA TRANSPORTATION AND ECONOMIC CORRIDORS  
 NORTH CENTRAL REGION - ATHABASCA AND FORT McMURRAY DISTRICTS  
 Hwy 754:06 WABASCA LAKE (NC110)  
 SPRING 2024

<b>Location:</b> Hwy 754:06 WABASCA LAKE <b>File Number:</b> 45363 <b>Probe:</b> RST Set 8R <b>Cable:</b> RST Set 8R	<b>Readout:</b> RST Set 8R <b>Casing Diameter:</b> 2.75" <b>Temp:</b> 16 <b>Read by:</b> NKR/NRM
---	---

**SLOPE INCLINOMETER (SI) READINGS**

SI#	GPS Location ( UTM 12)		Date	Stickup (m)	Readings Depth from top of casing (ft)	Azimuth of A+ Groove degree	Current Bottom Depth Readings				Size (")	Remarks
	Northing	Easting					A+	A-	B+	B-		
SI24-2	6206049	323068	13-Jun-24	-0.31	-60 to -2	225	0.001	-0.004	0.0244	-0.025	2.75	8 mm Allen Key Needed
SI24-3	6219684	467056	13-Jun-24	-0.23	-58 to -2	225	0.0712	0.0215	0.021	-0.0704	2.75	8 mm Allen Key Needed

**VIBRATING WIRE PIEZOMETER (VW) READINGS**

PN #	Serial	GPS Location ( UTM 12)		Location	Date	Reading		Comments
		Northing	Easting			B Unit	°C	
VW24-2A	171163	6206049	323068	Attached to TH24-2	13-Jun-24	No Reading**	4.7	8 mm Allen Key Needed
VW24-2B	163823	6206049	323068	Attached to TH24-2	13-Jun-24	8631.9	3.4	8 mm Allen Key Needed
VW24-3A	171177	6219684	467056	Attached to TH24-3	13-Jun-24	8787.4	3.6	8 mm Allen Key Needed
VW24-3B	163840	6219736	467059	Attached to TH24-3	13-Jun-24	8601.2	4.7	8 mm Allen Key Needed



SP#	GPS Location ( UTM 12)		Date	Stick-up (m)	Water level below top of pipe (m)	Comments
	Northing	Easting				
SP24-1	6219669	467009	13-Jun-24	-0.13	1.71	1/2" Socket Needed to Open
SP24-4	6215664	467132	13-Jun-24	-0.13	3.48	Allen key

**INSPECTOR REPORT**

8 mm Allen Key and 1/2" Socket needed to open flushmounts
** No Reading



H:\32000\32122 AT GRMP Athabasca and Fort McMurray Districts 2021-2025\CAD\32122 INSTRUMENT 2024\32122-NC110.dwg - 1N - Jul. 10. 2024



- LEGEND**
- APPROXIMATE TEST HOLE LOCATION
  - CRACK
  - ACTIVE HEADSCARP
  - TREE LINE
  - POWER LINE
  - GAS LINE
  - FIBRE CABLE
  - TELEPHONE LINE
  - ASPHALT PATCH
  - SLOPE INCLINOMETER
  - STANDPIPE PIEZOMETER
  - VIBRATING WIRE PIEZOMETER



AIR PHOTO FROM ESRI WORLD IMAGERY EXPORTED ON FEBRUARY 21, 2024



**NORTH CENTRAL  
(ATHABASCA AND FORT MCMURRAY DISTRICTS)**

**NC110 - WABASCA LAKE SLIP 'N' SLIDE  
HWY 754:06 WABASCA, ALBERTA  
SITE PLAN**


DWG No. 32122-NC110

DRAWN BY	ML
DESIGNED BY	JGP
APPROVED BY	TSA
SCALE	1:750
DATE	JULY 2024
FILE No.	32122






Thurber Engineering Ltd.



SI24-2, NC110 Wabasca Lake, Inclinator 24-2

Sets marked \* include zero shift and/or rotation corrections.


Thurber Engineering Ltd.



SI24-2, NC110 Wabasca Lake, Inclinometer 24-2

Sets marked \* include zero shift and/or rotation corrections.


Thurber Engineering Ltd.



SI24-2, NC110 Wabasca Lake, Inclinometer 24-2


Sets marked \* include zero shift and/or rotation corrections.

Thurber Engineering Ltd.




SI24-2, NC110 Wabasca Lake, Inclinometer 24-2

Thurber Engineering Ltd.



SI24-3, NC110 Wabasca Lake, Inclinometer 24-3


Thurber Engineering Ltd.



SI24-3, NC110 Wabasca Lake, Inclinometer 24-3




Thurber Engineering Ltd.




SI24-3, NC110 Wabasca Lake, Inclinator 24-3

Thurber Engineering Ltd.



SI24-3, NC110 Wabasca Lake, Inclinometer 24-3

**FIGURE NC110 -1  
HWY 754:06 (NC110) - WABASCA LAKE PIEZOMETER DEPTHS**



**FIGURE NC110-2  
HWY 754:06 (NC110) - WABASCA LAKE PIEZOMETER ELEVATIONS**

